

Environmental Information Sheet

Nativo® 75WG MAPP 16867



A water dispersible granule formulation containing 250 g/kg (25.0 % w/w) trifloxystrobin and 500 g/kg (50.0% w/w) tebuconazole. A broad spectrum systemic fungicide with protectant and curative properties for use on Brussels sprouts, cabbage, broccoli/calabrese, cauliflower and carrots.

Maximum individual dose: 0.36 kg/ha for Brussels sprouts, cabbage, cauliflower and broccoli/calabrese; 0.3 kg/ha for carrot.

Maximum number of applications: 2 for Brussels sprouts, cabbage, cauliflower and broccoli/calabrese; 3 kg/ha for carrot.

Section	Profile
1. WILDLIFE Mammals and Birds	Nativo 75WG is not classified as ' <i>Harmful to game, wild birds or animals</i> '. No risk management is necessary to protect mammals and birds. Trifloxystrobin and tebuconazole are of low or low/moderate toxicity to mammals and birds. The risk to wild mammals and birds grazing on treated areas is low, as is the risk due to exposure from other routes, e.g. consumption of insects.
2. BEES	No risk management is necessary. Nativo 75WG is of low risk to honeybees.
3. NON TARGET INSECTS AND OTHER ARTHROPODS	No risk management necessary. Nativo 75WG poses a low risk to the range of arthropod species commonly found in and around treated fields, e.g. ground beetles, lady birds and aphid parasitoids.
4. AQUATIC LIFE	Nativo 75WG is classified as Very toxic to aquatic life with long lasting effects. Do not contaminate surface waters or ditches with chemical or used container. Nativo can be used safely providing care is taken to prevent spray drift reaching surface waters. The following risk management practices must be carried out in order to ensure adequate protection for aquatic species. To protect aquatic organisms, respect an unsprayed buffer zone of 12m to surface water bodies. HORIZONTAL BOOM SPRAYERS MUST BE FITTED WITH THREE STAR DRIFT REDUCTION TECHNOLOGY. Low drift spraying equipment must be operated according to the specific conditions stated in the official three star rating for that equipment as published on HSE Chemicals Regulation Directorate's website. Maintain three star operating conditions until 30 m from the top of the bank of any surface water bodies. DO NOT ALLOW DIRECT SPRAY from horizontal boom sprayers to fall within 12m to the top of the bank of a static or flowing water body, or within 1 m of the top of a ditch which is dry at the time of application. Aim spray away from water. Buffer zone may not be reduced.

The
Voluntary
Initiative

February 2017